

Kathleen Hartnett White, *Chairman*
Larry R. Soward, *Commissioner*
Glenn Shankle, *Executive Director*



TEXAS COMMISSION ON ENVIRONMENTAL QUALITY
Protecting Texas by Reducing and Preventing Pollution

March 23, 2007

MR STEVEN G BURROWS
CHIEF ENVIRONMENTAL DIVISION
US DEPARTMENT OF THE ARMY
IMSW-HOD-PWE BLDG 4219 77TH ST
FORT HOOD TX 76544-5057

Permit by Rule Registration Number: 81233
Location/City/County: Us Highway 190 West Of Killeen Texas, Fort Hood, Bell County
Project Description/Unit: Fort Hood Army Base - Safety Certification Unit for Small Arms Brass
Regulated Entity Number: RN101612083
Customer Reference Number: CN600126262
New or Existing Site: Existing
Affected Permit (if applicable): 24538
Renewal Date (if applicable): None

US Department of the Army has registered the emissions associated with the Fort Hood Army Base - Safety Certification Unit For Small Arms Brass under Title 30 Texas Administrative Code §§ 106.261 and 106.262.

For rule information see www.tceq.state.tx.us/permitting/air/nav/numerical_index.html.

The company is also reminded that these facilities may be subject to and must comply with other state and federal air quality requirements. This registration is authorized on behalf of the TCEQ Executive Director. If you have questions, please contact Ms. Rahel Tadesse at (713) 767-3770.

Sincerely,

A handwritten signature in black ink, appearing to read "Anne M. Inman".

Anne M. Inman, P.E., Manager
General/Standard/Rule (GSR) Permit Section
Air Permits Division

Represented Emissions:

VOCs	<0.01	tpy
HAPs (included in VOC)		tpy
SO ₂	<0.01	tpy
CO	0.25	tpy
NO _x	0.16	tpy
PM	0.01	tpy

cc: Air Section Manager, Region 9 - Waco

Project Number: 127706

<<Prev Rule

Texas Administrative Code

Next Rule>>

TITLE 30

ENVIRONMENTAL QUALITY

PART 1

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

CHAPTER 106

PERMITS BY RULE

SUBCHAPTER K

GENERAL

RULE §106.261

Facilities (Emission Limitations)

(a) Except as specified under subsection (b) of this section, facilities, or physical or operational changes to a facility, are permitted by rule provided that all of the following conditions of this section are satisfied.

(1) The facilities or changes shall be located at least 100 feet from any recreational area or residence or other structure not occupied or used solely by the owner or operator of the facilities or the owner of the property upon which the facilities are located.

(2) Total new or increased emissions, including fugitives, shall not exceed 6.0 pounds per hour (lb/hr) and ten tons per year of the following materials: acetylene, argon, butane, crude oil, refinery petroleum fractions (except for pyrolysis naphthas and pyrolysis gasoline) containing less than ten volume percent benzene, carbon monoxide, cyclohexane, cyclohexene, cyclopentane, ethyl acetate, ethanol, ethyl ether, ethylene, fluorocarbons Numbers 11, 12, 13, 14, 21, 22, 23, 113, 114, 115, and 116, helium, isohexane, isopropyl alcohol, methyl acetylene, methyl chloroform, methyl cyclohexane, neon, nonane, oxides of nitrogen, propane, propyl alcohol, propylene, propyl ether, sulfur dioxide, alumina, calcium carbonate, calcium silicate, cellulose fiber, cement dust, emery dust, glycerin mist, gypsum, iron oxide dust, kaolin, limestone, magnesite, marble, pentaerythritol, plaster of paris, silicon, silicon carbide, starch, sucrose, zinc stearate, or zinc oxide.

(3) Total new or increased emissions, including fugitives, shall not exceed 1.0 lb/hr of any chemical having a limit value (L) greater than 200 milligrams per cubic meter (mg/m³) as listed and referenced in Table 262 of §106.262 of this title (relating to Facilities (Emission and Distance Limitations)) or of any other chemical not listed or referenced in Table 262. Emissions of a chemical with a limit value of less than 200 mg/m³ are not allowed under this section.

(4) For physical changes or modifications to existing facilities, there shall be no changes to or additions of any air pollution abatement equipment.

(5) Visible emissions, except uncombined water, to the atmosphere from any point or fugitive source shall not exceed 5.0% opacity in any six-minute period.

(6) For emission increases of five tons per year or greater, notification must be provided using Form PI-7 within ten days following the installation or modification of the facilities. The notification shall include a description of the project, calculations, data identifying specific chemical names, limit values, and a description of pollution control equipment, if any.

(7) For emission increases of less than five tons per year, notification must be provided using either:

(A) Form PI-7 within ten days following the installation or modification of the facilities. The notification shall include a description of the project, calculations, data identifying specific chemical

names, limit values, and a description of pollution control equipment, if any; or

(B) Form PI-7 by March 31 of the following year summarizing all uses of this permit by rule in the previous calendar year. This annual notification shall include a description of the project, calculations, data identifying specific chemical names, limit values, and a description of pollution control equipment, if any.

(b) The following are not authorized under this section:

(1) construction of a facility authorized in another section of this chapter or for which a standard permit is in effect; and

(2) any change to any facility authorized under another section of this chapter or authorized under a standard permit.

Source Note: The provisions of this §106.261 adopted to be effective March 14, 1997, 22 TexReg 2439; amended to be effective December 24, 1998, 23 TexReg 12925; amended to be effective September 4, 2000, 25 TexReg 8653; amended to be effective November 1, 2003, 28 TexReg 9279

[Next Page](#)

[Previous Page](#)

[List of Titles](#)

[Back to List](#)

[HOME](#) | [TEXAS REGISTER](#) | [TEXAS ADMINISTRATIVE CODE](#) | [OPEN MEETINGS](#) | [HELP](#) |

<<Prev Rule

Texas Administrative Code

Next Rule>>

TITLE 30

ENVIRONMENTAL QUALITY

PART 1

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

CHAPTER 106

PERMITS BY RULE

SUBCHAPTER K

GENERAL

RULE §106.262

Facilities (Emission and Distance Limitations)

(a) Facilities, or physical or operational changes to a facility, are permitted by rule provided that all of the following conditions of this section are satisfied.

(1) Emission points associated with the facilities or changes shall be located at least 100 feet from any off-plant receptor. Off-plant receptor means any recreational area or residence or other structure not occupied or used solely by the owner or operator of the facilities or the owner of the property upon which the facilities are located.

(2) New or increased emissions, including fugitives, of chemicals shall not be emitted in a quantity greater than five tons per year nor in a quantity greater than E as determined using the equation $E = L/K$ and the following table.

Attached Graphic

Attached Graphic

(3) Notification must be provided using Form PI-7 within ten days following the installation or modification of the facilities. The notification shall include a description of the project, calculations, and data identifying specific chemical names, L values, D values, and a description of pollution control equipment, if any.

(4) The facilities in which the following chemicals will be handled shall be located at least 300 feet from the nearest property line and 600 feet from any off-plant receptor and the cumulative amount of any of the following chemicals resulting from one or more authorizations under this section (but not including permit authorizations) shall not exceed 500 pounds on the plant property and all listed chemicals shall be handled only in unheated containers operated in compliance with the United States Department of Transportation regulations (49 Code of Federal Regulations, Parts 171-178): acrolein, allyl chloride, ammonia (anhydrous), arsine, boron trifluoride, bromine, carbon disulfide, chlorine, chlorine dioxide, chlorine trifluoride, chloroacetaldehyde, chloropicrin, chloroprene, diazomethane, diborane, diglycidyl ether, dimethylhydrazine, ethyleneimine, ethyl mercaptan, fluorine, formaldehyde (anhydrous), hydrogen bromide, hydrogen chloride, hydrogen cyanide, hydrogen fluoride, hydrogen selenide, hydrogen sulfide, ketene, methylamine, methyl bromide, methyl hydrazine, methyl isocyanate, methyl mercaptan, nickel carbonyl, nitric acid, nitric oxide, nitrogen dioxide, oxygen difluoride, ozone, pentaborane, perchloromethyl mercaptan, perchloryl fluoride, phosgene, phosphine, phosphorus trichloride, selenium hexafluoride, stibine, liquified sulfur dioxide, sulfur pentafluoride, and tellurium hexafluoride. Containers of these chemicals may not be vented or opened directly to the atmosphere at any time.

(5) For physical changes or modifications to existing facilities, there shall be no changes or additions of air pollution abatement equipment.

(6) Visible emissions, except uncombined water, to the atmosphere from any point or fugitive source shall not exceed 5.0% opacity in any six-minute period.

(b) The following are not authorized under this section except as noted in subsection (c) of this section:

(1) construction of a facility authorized in another section of this chapter or for which a standard permit is in effect; and

(2) any change to any facility authorized under another section of this chapter or authorized under a standard permit.

(c) If a facility has been authorized under another section of this chapter or under a standard permit, subsection (a)(2) and (3) of this section may be used to qualify the use of other chemicals at the facility.

Source Note: The provisions of this §106.262 adopted to be effective March 14, 1997, 22 TexReg 2439; amended to be effective December 24, 1998, 23 TexReg 12925; amended to be effective September 4, 2000, 25 TexReg 8653; amended to be effective November 1, 2003, 28 TexReg 9279

[Next Page](#)

[Previous Page](#)

[List of Titles](#)

[Back to List](#)

[HOME](#) | [TEXAS REGISTER](#) | [TEXAS ADMINISTRATIVE CODE](#) | [OPEN MEETINGS](#) | [HELP](#) |

Figure 1: 30 TAC §106.262(a)(2)

<u>D. Feet</u>	<u>K</u>	
100	326	E = maximum allowable hourly emission, and never to exceed 6 pounds per hour.
200	200	
300	139	
400	104	
500	81	L = value as listed or referenced in Table 262
600	65	
700	54	
800	46	K = value from the table on this page. (interpolate intermediate values)
900	39	
1,000	34	
2,000	14	D = distance to the nearest off-plant receptor.
3,000 or more	8	

Figure 2: 30 TAC §106.262(a)(2)

TABLE 262
LIMIT VALUES (L) FOR USE WITH EXEMPTIONS FROM PERMITTING §106.262

The values are not to be interpreted as acceptable health effects values relative to the issuance of any permits under Chapter 116 of this title (relating to Control of Air Pollution by Permits for New Construction or Modification).

<u>Compound</u>	<u>Limit (L)</u> <u>Milligrams Per Cubic Meter</u>
Acetone	590.
Acetaldehyde	9.
Acetone Cyanohydrin	4.
Acetonitrile	34.
Acetylene	2662.
N-Amyl Acetate	2.7
Sec-Amyl Acetate	1.1
Benzene	3.
Beryllium and Compounds	0.0005
Boron Trifluoride, as HF	0.5
Butyl Alcohol, -	76.
Butyl Acrylate	19.
Butyl Chromate	0.01
Butyl Glycidyl Ether	30.
Butyl Mercaptan	0.3
Butyraldehyde	1.4
Butyric Acid	1.8
Butyronitrile	22.
Carbon Tetrachloride	12.

Chloroform	10.
Chlorophenol	0.2
Chloroprene	3.6
Chromic Acid	0.01
Chromium Metal, Chromium II and III Compounds	0.1
Chromium VI Compounds	0.01
Coal Tar Pitch Volatiles	0.1
Creosote	0.1
Cresol	0.5
Cumene	50.
Dicyclopentadiene	3.1
Diethylaminoethanol	5.5
Diisobutyl Ketone	63.9
Dimethyl Aniline	6.4
Dioxane	3.6
Dipropylamine	8.4
Ethyl Acrylate	0.5
Ethylene Dibromide	0.38
Ethylene Glycol	26.
Ethylene Glycol Dinitrate	0.1
Ethylidene-2-norbornene, 5-	7.
Ethyl Mercaptan	0.08
Ethyl Sulfide	1.6
Glycolonitrile	5.
Halothane	16
Heptane	350.
Hexanediamine, 1,6-	0.32

Hydrogen Chloride	1.
Hydrogen Fluoride	0.5
Hydrogen Sulfide	1.1
Isoamyl Acetate	133.
Isoamyl Alcohol	15.
Isobutyronitrile	22.
Kepone	0.001
Kerosene	100.
Malononitrile	8.
Mesityl Oxide	40.
Methyl Acrylate	5.8
Methyl Amyl Ketone	9.4
Methyl-t-butyl ether	45.
Methyl Butyl Ketone	4.
Methyl Disulfide	2.2
Methylenebis (2-chloroaniline) (MOCA)	0.003
Methylene Chloride	26.
Methyl Isoamyl Ketone	5.6
Methyl Mercaptan	0.2
Methyl Methacrylate	34.
Methyl Propyl Ketone	530.
Methyl Sulfide	0.3
Mineral Spirits	350.
Naphtha	350.
Nickel, Inorganic Compounds	0.015
Nitroglycerine	0.1
Nitropropane	5.

Octane	350.
Parathion	0.05
Pentane	350.
Perchloroethylene	33.5
Petroleum Ether	350
Phenyl Mercaptan	0.4
Propionitrile	14.
Propyl Acetate	62.6
Propylene Oxide	20.
Propyl Mercaptan	0.23
Silica-amorphous- precipitated, silica gel	4.
Silicon Carbide	4.
Stoddard Solvent	350.
Styrene	21.
Succinonitrile	20.
Tolidine	0.02
Trichloroethylene	135.
Trimethylamine	0.1
Valeric Acid	0.34
Vinyl Acetate	15.
Vinyl Chloride	2.

NOTE: The time weighted average (TWA) Threshold Limit Value (TLV) published by the American Conference of Governmental Industrial Hygienists (ACGIH), in its TLVs and BEIs guide (1997 Edition) shall be used for compounds not included in the table. The Short Term Exposure Level (STEL) or Ceiling Limit (annotated with a "C") published by the ACGIH shall be used for compounds that do not have a published TWA TLV. This section cannot be used if the compound is not listed in the table or does not have a published TWA TLV, STEL, or Ceiling Limit in the ACGIH TLVs and BEIs guide.